

13 APR 2005

531, 133

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/047616 A1

- (51) International Patent Classification⁷: E04D 13/076 (81) Designated States (*national*): AU, CA, CN, JP, NZ, US, ZA.
- (21) International Application Number: PCT/AU2003/001516 (84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (22) International Filing Date: 14 November 2003 (14.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant and
(72) Inventor: CROSSLEY, William, James [AU/AU]; 16 Mooloolah Drive, Minyama, QLD 4575 (AU).
- (74) Agent: M PULLEN, Kevin; Patent & Trade Mark Attorney, PO Box 241, Landsborough, QLD 4550 (AU).
- Declarations under Rule 4.17:**
— as to the identity of the inventor (Rule 4.17(i)) for the following designations AU, CA, CN, JP, NZ, ZA, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR) of inventorship (Rule 4.17(iv)) for US only
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: GUTTER CLEANING SHUTTER



(57) **Abstract:** A gutter cleaning shutter, made from a durable material, is disclosed. It consists of a rigid frame (1) with an internal sliding plate (2). The shutters are fitted to the ends of roof gutters (3) instead of gutter stop ends. The gutter cleaning shutter with sliding plate in place provides normal gutter operation. Opening the sliding plate provides an unobstructed outlet to enable gutters to be cleaned by propelling accumulated rubbish along the gutter and out through the open shutter frame. A strong jet of water from a garden hose would be the recommended method of propelling the rubbish during cleaning. Sealing plates (5) are placed over the tops of downpipes to prevent rubbish falling into the drainage system. When cleaning is completed the sealing plates (5) are removed, and the sliding plate (2) in the cleaning shutter frame (1) closed restoring the normal operation of the roof drainage system.

WO 2005/047616 A1